

ELCOMAN S.R.L.

KOBRA 390 S5 E/S

KOBRA

99.641

Heavy duty "Energy Smart" Office shredder

KOBRA 390 S5

Throat width: 400 mm Security Level DIN 66399: P-2 O-2 T-2 E-2

Security Level DIN 32757: 2

Shred size: 5,8mm straight cut

Paper capacity*: 31-33 A4/70gr; 28-30 A4/80gr sheets
Shreddable material: Paper, Credit Cards, Credit Cards with chip,

CD/DVD, Floppy

Speed: 0,09 m/sec
Noise level (idle/shredding): 59/60 dba
Voltage: 230 V

Power: 920 Watt (2 motors per 460W each)

Waste bag capacity: 200 liters
Dimensions (WxDxH): 60x48x93cm
Net Weight: 73Kg



Manufacturer: Brand:

Model: Article code:






Office straight cut shredder designed to shred large quantities of computer print-outs. Equipped with "ENERGY SMART" system with efficient illuminated indicators for **power saving stand-by mode** and **environmental protection**. A **double motor** drive technology, operating in conjunction with **two** "SUPER POTENTIAL POWER UNIT", delivers maximum performances. 200-liter high quality steel cabinet holds high volume of shredded materials.

24 hours continuous duty motor

- Two heavy duty chain drive with steel gears "SUPER POTENTIAL POWER UNIT"
- Automatic Start/Stop through electronic eyes
- Automatic Stop when shred bag is full and electronic door safety switch
- Automatic Stop and reverse in case of paper jams
- Carbon hardened cutting head takes staples and paper clips
- 200 liters high quality steel cabinet
- Mounted on casters
- Motor thermal protection
- Accessories: document top shelf code 99.003, plastic waste bags (50 pcs.) code 99.203
- Certification marks: CB CSA CE
- Manufacturer: Elcoman Via Gorizia nº 9, 20813 Bovisio Masciago MB Italy
- Packaging: 1 unit per box
- EAN Barcode 8 026064 996419



"ENERGY SMART"

Management system for power saving stand-by mode



Adjustable computer forms top shelf (Space Saving Design). Integrated sliding flap makes Floppy-Disks and CDs shredding easy



 $^{^{\}star}$ Capacity varies on supply power, weight, quality and grain of paper, operating temperature and blade lubrication