

Specifications

Scanning Face	Simplex / Duplex
Scanning Method	1 line Colour CIS (300 dpi/600 dpi), Black or White Background
Scanning Resolution*1	100 – 600 dpi (1 dpi step) and 1,200 dpi (interpolated) Optical: 300 dpi / 600 dpi (Automatic switch)
Scanning Speed*2	Binary/Colour A4/Portrait, 200/300 dpi KV-N1058X Simplex: Up to 65 ppm, Duplex: Up to 130 ipm KV-N1028X Simplex: Up to 45 ppm, Duplex: Up to 90 ipm
Output Methods	Scan to Email, Scan to FTP, Scan to Shared Folder, Scan to Cloud*3, Scan to SharePoint*3, Scan to PC*4
Double-Feed Detection	Ultrasonic (The length of documents that can be detected is 70 mm (2.8 in.) or more.)
Image Compression	MH, MMR, JPEG, JPEG2000
Binary Mode Halftone	Dither, Error Diffusion
Image Control	Auto Preview, Auto Rescan, Automatic Brightness Adjustment, Multi Colour Drop Out, Dynamic Threshold, White Level From Paper, Image Emphasis Gamma, Automatic Separation, Noise Reduction
Other Functions	Length Control, Barcode Detection, Patchcode Detection (Type 2, 3, T), Control Sheet Detection, Long Paper, Double Feed Skip
Documents	Width Length Thickness
Card	Weight Format Size Thickness
Feed Tray Capacity	100 sheets: 80 g/m ² (21 lb.) High-quality woodfree paper*7
Supported Operating System	Windows Vista® SP2 (32 bit/64 bit), Windows® 7 (32 bit/64 bit), Windows® 8 (32 bit/64 bit), Windows® 8.1 (32 bit/64 bit), Windows® 10 (32 bit/64 bit), Windows Server® 2003 SP2 (32 bit/64 bit), Windows Server® 2003 R2 SP2 (32 bit/64 bit), Windows Server® 2008 SP2 (32 bit/64 bit), Windows Server® 2008 R2 SP1 (64 bit), Windows Server® 2012 (64 bit), Windows Server® 2016 (64 bit)
Recommended Web Browser	Internet Explorer 11, Mozilla Firefox (latest version), Google Chrome (latest version)
Interface	USB 3.1 Gen1 (backward compatible) LAN (10Base-T / 100Base-TX / 1000Base-T) *8 Wireless LAN (IEEE802.11n/g/b)
Wireless LAN	Communication standard Frequency range** (center frequency) / Channel
External Dimensions (W X D X H)	300 mm x 272 mm x 238 mm (11.8 in. x 10.7 in. x 9.4 in.) (When the exit tray is closed)
Weight	4.1 kg (9.0 lb.)
Power Requirement**10	AC 100 – 127 V, 50/60 Hz, 0.8 A AC 220 – 240 V, 50/60 Hz, 0.4 A
Power Consumption	Maximum (Scanning) Minimum (Ready) Sleep Power off
Operating Environment	Temperature: 5 °C – 35 °C (41 °F – 95 °F) Humidity: 20 % – 80 % RH
Storage Environment	Temperature: -10 °C – 50 °C (14 °F – 122 °F) Humidity: 8 % – 75 % RH
Accessories	CD-ROM: Device Driver, ISIS driver software, TWAIN driver software, User utility, Scan Button Setting Tool*12, Image Capture Plus, Operating Manual, Control sheet Quick Installation Guide, Power cord, USB cable (1.5 m (59 in.) / USB 3.1), Mixed batch card guide, Anti glare film (for **-M model)
Options	Flatbed Scanner: KV-SS081*13, Roller exchange kit: KV-SS061, Roller cleaning paper: KV-SS03, Carrier Sheet: KV-SS077, Image Capture Plus add-in (single license package): KV-SS092*14, Image Capture Plus add-in (10 license package): KV-SS093*15, Image Capture Plus OCR module for network scan 10-user license package: KV-SS094*16

Dimensions



- *1 When scanning a document larger than A5 size at resolutions over 600 dpi, the scanning may fail due to insufficient memory.
- *2 The scanning speed is the maximum speed of the scanner hardware. It does not include software processing time, data transfer time, etc. The scanning speed measurement is based on Panasonic's measuring method. In case of using this unit with a LAN connection, the scanning speed may be slower due to network traffic.
- *3 Scan server must be set up. Also, it is necessary to install Image Capture Plus into the PC used as a scan server.
- *4 It is necessary to install Image Capture Plus into the target PC.
- *5 Using "Long Paper", you can scan a long document to a series of split scanned images.
- *6 Use the carrier sheet (KV-SS077) to scan passport. Depending on the condition (operating environment, dirt, scratches, etc.) of the carrier sheet or passport, the image processing function may not work properly. Scan beforehand to confirm the scanned image.
- *7 Paper less than 100 mm (3.9 in.) long or legal size paper: 75 sheets
- *8 To assure continued emission limit compliance, use only shielded LAN cable. The cable should be a CAT 5 (Category 5) or higher for 10Base-T / 100Base-TX, or CAT 5e (Enhanced Category 5) or higher for 1000Base-T.
- *9 Values differ depending on the country.
- *10 The power requirement differs depending on the country/area.
- *11 If connected to a network device (hub, router, etc.) that supports IEEE802.3az.
- *12 This tool is used when the scanner is connected via USB.
- *13 USB Scanning only.
- *14 Required to installing OCREngine for Image Capture Plus on 2 or more PCs.
(For 1 license)
- *15 Required to installing OCREngine for Image Capture Plus on 2 or more PCs.
(For 10 licenses)
- *16 To install the scan server, you need this option.

Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.
- ISIS is a registered trademark or trademark of EMC Corporation in the United States and other countries.
- Windows, Windows Vista, Windows Server and Internet Explorer are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- Mozilla and Firefox are registered trademarks of the Mozilla Foundation.
- Google and Google Chrome are either trademarks or registered trademarks of Google LLC.
- All other brand or product names are the property of their respective holders.

This product is designed to reduce hazardous chemical substances in accordance with the RoHS directive.

- * The power requirement differs depending on the country/area
- All photographs in this brochure are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.


Panasonic

Document Scanner

KV-N1058X

KV-N1028X

Securely Share Scanned Data with Easy-to-Use Network Scanner



1.800.635.3587
panasonic.com

Panasonic is constantly enhancing product specifications and accessories. Specifications subject to change without notice. Trademarks are property of their respective owners. ©2018 Panasonic Corporation of North America. All rights reserved.

Panasonic



Large Colour Touch Screen

Flexible Network Connectivity

Advanced Network Security



